

## iDS-TCW403-BI 4 MP IR ANPR Container No. Recognition Camera



- High performance Container No. Recognition bullet camera
- High quality imaging with 4 MP resolution(1/1.8" CMOS)
- Clear imaging against strong back light due to 140 dB WDR technology
- Excellent low-light performance with DarkFighter technology
- Motorized vari-focal lens for easy installation and monitoring
- Efficient H.265 compression technology
- Smart functions: supports container No. recognition and ISO No. recognition
- Water and dust resistant (IP67)

## ▪ Specification

<b>Camera</b>	
Image Sensor	1/1.8" Progressive Scan CMOS
Max. Resolution	2688 × 1520
Min. Illumination	Color: 0.001 Lux @ (F1.2, AGC ON), B/W: 0.0001 Lux with IR
Shutter Time	1 s to 1/100000 s
Slow Shutter	Yes
<b>Lens</b>	
Focal Length & FOV	4 to 11 mm, horizontal FOV 114.7° to 41.9°, vertical FOV 59.4° to 23.6°, diagonal FOV 141.5° to 48.1°
Focus	Auto
Iris Type	Auto-iris: DC drive
Aperture	F1.38
<b>Video</b>	
Video Compression	Main stream: H.265/H.264/MJPEG, Sub-stream: H.265/H.264/MJPEG
Video Bit Rate	32 Kbps to 16 Mbps
H.264 Type	Baseline Profile, Main Profile, High Profile
H.265 Type	Baseline Profile, Main Profile, High Profile
<b>Network</b>	
Protocols	ISAPI, GB28181, HIKVISION SDK
<b>Image</b>	
Frame Rate	25 fps
Wide Dynamic Range (WDR)	140 dB
Image Enhancement	3D DNR
<b>Interface</b>	
Video Output	Network
Ethernet Interface	1 RJ45 10/100/1000 M self-adaptive Ethernet port(s)
On-Board Storage	Built-in memory card slot, support micro TF card, up to 128 GB. The memory card needs to be installed before leaving the factory.
Alarm	1 output interface
RS-485	1 RS-485
<b>Road Traffic and Vehicle Detection</b>	
Smart Function	Container No. Recognition and ISO No. Recognition
<b>General</b>	
Operating System	Linux
Power	24 VAC, max. 15 W
Material	Aluminum alloy
Dimension	298.4 mm × 115.5 mm × 110.8 mm (11.75" × 4.55" × 4.36")
Weight	2 ± 0.5 kg (4.41 ± 1.1) lb.
Operating Condition	-30 °C to 70 °C (-22 °F to 158 °F). Humidity 95% or less (non-condensing)
<b>Approval</b>	
Protection	IP67: IEC 60529-2013

▪ **Available Model**

iDS-TCW403-BI/GK/0411

**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision\_Global



Hikvision  
Corporate Channel



hikvisionhq